



Spotwelding Consultants, Inc.

4209 Industrial

Rowlett, TX 75088

Phone: 972-475-0874 **Fax:** 972-475-5024

Website: www.spotweldingconsultants.com

Product # R1000-XXX, R1000 Cooling System

Specifications:

- Factory set at 50 psi adjustable to 80 psi
- 3 gallon reservoir
- 115 or 230 VAC / 1 ph-50 / 60 Hz
- 5.6 / 2.8 amp: 60 Hz
- 14,000 BTU
- Dimensions: 23"L x 11 "W x 14.75"H
- 1/4" FPT (water in / out) with 5/8" LH Standard Inert Gas Fitting
- 8 foot power cord
- Visible water level and flow sight glass
- Thermal overload
- Net weight:42 lbs / 19 kg
- Foam packed for UPS shipment

R1000: Rotary GEAR Pump (only)

- 1.8 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump (Repair Kit Product No. P5001)



ADDITIONAL INFORMATION

| | |
|------------------------|--|
| <p>System Features</p> | <ul style="list-style-type: none"> • Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions. <ul style="list-style-type: none"> • All units are plumbed with copper tubing and reinforced hose. <ul style="list-style-type: none"> • New extended life pump • No external plumbing is required because of closed loop water system. • A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance. |
|------------------------|--|