

FLEX-CABLE/NCSI AIR-COOLED CABLE ORDER FORM

MCM SIZE	TYPE	STYLE	HOLE DIAMETERS	LENGTH IN INCHES	OPTIONS
<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>
- S					

MCM SIZE
40 = 400MCM
50 = 500MCM
60 = 600MCM
75 = 750MCM
10 = 1000MCM
12 = 1200MCM
15 = 1500MCM
20 = 2000MCM

CABLE TYPE
A = COLOR-FLEX
X = FLEXTRA
I = IW-FLEX

STYLE
 See Terminal Configuration Chart

HOLE DIAMETERS
1717 = 17/32" and 17/32"
1721 = 17/32" and 21/32"
2121 = 21/32" and 21/32"
x x x x = CUSTOMER SPECIFIED HOLE DIAMETERS


LENGTH IN INCHES
 PLEASE SPECIFY

OPTIONS
WK = 1 3/8" terminal width for 400-750 MCM sizes.
P = PERFORATED COVER
E = EXTENDED COLLAR

EXAMPLE: **12AA1721-18-S**
DESCRIPTION: **18 in. 1200MCM COLOR-FLEX WITH 17/32" & 21/32" HOLES IN SILVER PLATED TERMINALS.**

AIR-COOLED TERMINAL CONFIGURATION CHART

Standard terminal width is 1-1/4 in. 1-3/8 in. and 1-1/2 in. are available upon request.
See ordering chart for bolt hole diameters.



"B"
Thickness

MCM	STANDARD			
	Width	1-1/4	1-3/8	1-1/2
400		0.38	0.35	---
500		0.44	0.41	---
600		0.50	0.46	---
750		0.63	0.58	---
1000		0.81	0.74	0.67
1200		0.97	0.88	0.81
1500		1.22	1.11	1.02
2000		---	---	---

