



**FEATURES AND SPECIFICATIONS**

**Features and Benefits**

- Long life nut welding electrode system with retractable locators
- Replaceable insulated stainless steel locator pins
- Replaceable long life ELKONITE® face
- For threaded holders
- For 4mm-6mm & #4-1/4” nuts

**Use With**


- Threaded adapters in platen mounted holder in special fixtures

**Mechanical**

- Accepts external cooling chambers\*



\*External Electrode Cooling Chamber



ELECTRODES  
STUD/NUT

**ORDERING INFORMATION AND DIMENSIONS**

TAPER	SCREW THREAD SIZE	PIN DIA. P	PART NO.	CMW®3 BASE	SPRING	CERAMIC COATED STAINLESS STEEL PIN	ELKONITE® 10W3 FACED CAP	USE WITH COOLING CHAMBER*
RWMA 5	#4	0.142	16-37725-04	16-37325	16-950078-01	16-950064-04	16-37725-C04	18-1340
	#5	0.158	16-37725-05	16-37325	16-950078-01	16-950064-05	16-37725-C05	
	#6	0.173	16-37725-06	16-37325	16-950078-01	16-950064-06	16-37725-C06	
	4 mm	0.187	16-37725-M4	16-37325	16-950078-01	16-950064-M4S	16-37725-CM4	
	#8	0.198	16-37725-08	16-37325	16-950078-01	16-950064-08	16-37725-C08	
	#10	0.220	16-37725-10	16-37325	16-950078-01	16-950064-10	16-37725-C10	
	5 mm	0.226	16-37725-M5	16-37325	16-950078-01	16-950064-M5S	16-37725-CM5	
	#12	0.250	16-37725-12	16-37325	16-950078-01	16-950064-12	16-37725-C12	
	6 mm	0.266	16-37725-M6	16-37325	16-950078-01	16-950064-M6S	16-37725-CM6	
0.250	0.283	16-37725-25	16-37325	16-950078-01	16-950064-25	16-37725-C25		