



Spotwelding Consultants, Inc.

4209 Industrial

Rowlett, TX 75088

Phone: 972-475-0874 Fax: 972-475-5024

Website: www.spotweldingconsultants.com

Product # R2000-XXX/X, R2000 Cooling System

Specifications:

- Factory set at 50 psi adjustable to 100 psi
- 6 gallon reservoir (15 gallon available)
- 115 VAC 50 / 60 Hz 1 ph
- 230 VAC 50 / 60 Hz 1 ph
- 13.4 / 6.7 amp:60 Hz 1 ph
- 230 / 190 VAC 50 / 60 Hz 3 ph
- 460 / 380 VAC 50/60 Hz 3 ph
- 2.6 / 1.3 amp:60 Hz3 ph
- 30,000 BTU
- Dimensions: 23"L x 16"W x 19.5"H
- 1/4" FPT (water in / out) with 5/8" LH Standard Inert Gas Fitting
- 8 foot power cord. 1 ph only
- Visible water level / water flow sight glass
- Thermal overload
- Net weight: 68 lbs/31 kg
- Foam packed for UPS shipment

R2000: Rotary GEAR Pump (only)

- 3.5 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump (Repair Kit Product No. P2001)



ADDITIONAL INFORMATION

System Features	<ul style="list-style-type: none"> • Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions. • All units are plumbed with copper tubing and reinforced hose.
-----------------	---