

JT Series

Model	Electrical	BTU/Hr 65° F	Watts/Hr 18° C	BTU/Hr 70° F	Watts/Hr 21° C	Pump Flow @ 50 psi HP	GPM	Rated Load Amps	Reservoir US Gal
180	115/160	1,690	495	2,350	689	0.25	2	13	7(26.5)
250	115/160	3,760	1,102	5,050	1,480	0.25	2	16	5(18.9)
500	115/160 230/160	5,040	1,477	6,888	2,016	0.33	4	20 10	5(18.9)
750	115/160 230/160	7,230	21,119	10,510	3,080	0.33	4	29 14	12(45.4)
1,000	130/160	11,360	3,330	13,960	4,092	0.33	4	14	12(45.42)

JT Dimensions

Model	Length in (cm)	Width in (cm)	Height in (cm)	Inlet & Outlet Piping NPT	Dry Wt. lbs (kg)
180	22 (55.88)	14 (35.56)	22 (58.88)	0.5	150 (68.04)
250	22 (55.88)	21 (53.32)	29 (73.66)	0.5	150 (68.04)
500	22 (55.88)	21 (53.34)	32 (81.28)	0.5	200 (90.72)
750	29 (73.66)	25 (63.50)	32 (81.28)	0.5	225 (102.06)
1,000	29 (73.66)	25 (63.50)	32 (81.28)	0.5	252 (113.4)